



Wired 2D barcode scanner

Features

- With quicker decode rate.
- Multi - selection for different usage.
- High resolution up to 5 mil.
- Multi-interfaces just by change cable.
- Optional: auto-sensing and hands-free stand.
- Suitable for Supermarket, POS (Point-of-sales), inventory management or Document tracking.



Scanners Specifications :

Model Name	LS6307M
Description	2D Barcode Scanner
Engine	2D engine

Performance Characteristics

• Light source	625±10 nm LED
• Depth of field	1D (13 mil EAN13) : 270 mm
• Sensor	CMOS (752x480 pixels)
• Best resolution	CODE39 ≥ 5mil
• Reading angle	Tilt: 360° / Pitch ±50° / Skew ±50°
• Print contrast	≥ 30%
• Indicators	LED & Beeper
• Interface	RS232, USB(Serial), USB (HID)
• Symbologies	Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN/ISSN, Code 93, UCC/EAN-128, GS1 Databar PDF417, QR Code, Data Matrix

Electrical Characteristics

• Input voltage	5 V/DC ± 0.5 V
• Current - operating	230 mA

Physical Characteristics

• Dimension (L *W *H)	165 X 65 X 90 mm
• Weight	110 g +/- 5 g (No cable)
• Case material	Rubber & ABS plastic

Environment

• Temperature-operation	0°C to 50°C
• Temperature-storage	-10°C to 60°C
• Humidity	5% to 95% relative humidity, non-condensing
• Ambient Light	0-100,000 lux (total darkness-bright sunlight)
• IP Rating	IP42

Depth of Field

• 13 mil EAN-13	30mm ~ 270mm
• 6.7 mil PDF 417	40mm ~ 135mm
• 10 mil DataMatrix	24mm ~ 130mm
• 15 mil QR code	10mm ~ 220mm

Product specification is subject to change without notice.

RIOTEC CO., LTD.

8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan

TEL : +886-2-8647-1828

FAX : +886-2-8647-1800

E-mail : sales@riotec.com.tw

Web : www.riotec.com.tw